



	A	B	C	D	E
310-6-1	14-1/2"	4-3/8"	1-13/16"	1-3/4"	1-3/4"
310-6-2	15-1/8"	5"	1-13/16"	1-3/4"	1-3/4"
310-6-3	15-3/4"	5-5/8"	1-13/16"	1-3/4"	1-3/4"
310-6-30	13-1/8"	3"	1-13/16"	1-3/4"	1-3/4"

Industrial grade electric strikes used on a pair of doors (without mullion) which are equipped with concealed, vertical-rod exit devices having a 1/2" or 5/8" throw latchbolt

300 Series

Applications



310-6-8

For only the active leaf of a pair

- PK keeper standard

310-6-1

For both leaves of a pair of doors - when spacing of the vertical rods is between 4" and 4-3/4"

- PK keeper standard

310-6-2

For both leaves of a pair of doors - when spacing of the vertical rods is between 4-5/8" and 5-3/8"

- PK keeper standard

310-6-3

For both leaves of a pair of doors - when spacing of the vertical rods is between 5-1/4" and 6"

- PK keeper standard

310-6-30

For both leaves of a pair of doors - when spacing of the vertical rods is between 2-5/8" and 3-3/8"

- PK keeper standard

Note: Double-door models are available with four different center-to-center dimensions between latchbolt keepers. Keepers are wide enough to compensate for vertical-rod exit bolts which may be as much as 3/8" (10mm) off center-to-center dimension, either way.

Note: When using an electric strike in conjunction with a vertical-rod exit device, it is necessary that:

1. The bottom rod of the exit device be removed or made inoperative
2. The latchbolt of the exit device be the "Pullman" or beveled type
3. The latchbolt be free-latching and remain projected while the door is open. Mechanisms that hold the latchbolt retracted while the door is open, and automatically release it when the door is closed, must be removed or made inoperative
4. Will not operate with deadbolt style rods.





FOLGER ADAM®
ASSA ABLOY

Specifications

- UL1034, burglary-resistant listed
- ANSI/BHMA A156.31, Grade 1
- DOD approved
- New York City accepted

Electrical

- .51 Amps @ 12VDC continuous duty
- .25 Amps @ 24VDC continuous duty

Standard Features

- Tamper resistant, heavy-duty construction
- Constructed entirely of stainless steel for strength and corrosion resistance
- Static strength 1,500 lbs.
- Dynamic strength 70 ft-lbs.
- Endurance 500,000 cycles
- Adjustable keeper to allow for door and frame misalignment
- Non-handed
- Fail Secure (standard)
- Plug-in connector
- Five year limited warranty

Optional Features

- Fail Safe
- LCBMA - Latchbolt & Locking Cam Monitor with Auxiliary Switch

Accessories

- 2001-1- Wire-in bridge rectifier
- 2001M - Plug-in bridge rectifier
- 2004M - ElectroLynx® adapter
- 2005M- SMART Pac II™
- 2006M - Plug-in buzzer

Finishes

- 612 - Satin bronze finish
- 627 - Satin aluminum finish

310-6-30

310-6-3

310-6-2

310-6-1

310-6-8