


# 4500C Series Electric Strike Complete Pac



Experience a safer  
and more open world

The 4500C series electric strike is designed for installation in 2" UL 10C fire rated frames with 1/2" drywall penetration. The 4500C features a low profile 1-3/8" depth, heavy-duty stainless steel construction. Its strength is derived from a unique keeper pin locking design, enabling the 4500C to exceed the ratings of the frame, door and locking hardware.



## Low Profile

- Maintains 1/2" drywall penetration, even in a 2" UL 10C fire-rated frame
- Strike body depth 1-3/8"
- Unique keeper locking pin design

## Heavy Duty Construction

- Exceeds ratings for most frames, doors and locking hardware
- Stainless steel construction
- ANSI/BHMA A156.31, Grade 1

## Convenient & Versatile

- Includes two faceplates to accommodate either cylindrical or mortise locksets up to a 3/4" throw latchbolt
- Full keeper shims for horizontal adjustment
- Field selectable fail secure/fail safe



Grade 1



SecuriCare  
Warranty



Mortise Locks  
without  
Deadbolt



Cylindrical  
Locksets



Field Selectable  
(Fail secure  
/Fail safe)



Dual Voltage  
12/24



PoE  
Friendly



Fire Rated



Burglary  
Rated

## Features

- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs.
- Dynamic strength 100 ft-lbs.
- Endurance 1,000,000 cycles
- Field selectable fail safe/fail secure
- Two faceplates provided to accommodate a variety of locksets
- Non-handed
- Internally mounted solenoid
- Accommodates up to a 3/4" latchbolt
- Strike body depth 1-3/8"
- Plug-in connector
- Trim enhancer
- Full keeper shims for horizontal adjustment
- Dual voltage 12 or 24 VAC/VDC

## Certifications

- ASTM E152 Fire Door Compliant
- ANSI/BHMA A156.31, Grade 1
- CAL FIRE, 3776-1654:0100
- NFPA-252 fire door Compliant
- California State Fire Marshal Listed (old)
- UL 1034 Burglary-Resistant Listed
- UL 10C Fire-Rated, 3 Hour Single Door [Fail Secure Only]
- UL 294 Listed

## Specifications

### Frame Application

- Metal
- Wood

### Electrical

- .24 Amps at 12 VDC/VAC
- .12 Amps at 24 VDC/VAC
- DC continuous duty  
AC intermittent duty only

## Options

- LBM - Latchbolt monitor
- LBSM - Latchbolt strike monitor

## Accessories

- 157 Torx® screws
- 150 Strike Latch Guard
- HES-CUT-MTK Metal Template Kit
- 2005M3 SMART Pac® III
- 4500-105 Trim Enhancer
- 4500-110 Replacement Strike Plate
- 4500-131 Filler Block
- 2001M Plug-in Bridge Rectifier
- 2004M ElectroLynx® adapter
- 2006M Plug-in Buzzer
- 4501-1/2 Lip Extension
- 4501-1 Lip Extension

## Dimensions




Diagram shown with cylindrical faceplate

## How to Order

SERIES	FINISH	OPTION (S)
<b>4500C</b>	<b>- 630</b>	<b>- LBM</b>
<b>4500C</b> Complete Electric Strike; includes faceplates for cylindrical and mortise locks	<b>605</b> Bright Brass <b>606</b> Satin Brass <b>612</b> Satin Bronze <b>613</b> Bronze Toned <b>629</b> Bright Stainless Steel <b>630</b> Satin Stainless Steel	<b>(blank)</b> No Monitor <b>LBM</b> Latchbolt Monitor <b>LBSM</b> Latchbolt Strike Monitor