



MODEL	A	B	C
MUNL	3.625	1.25	1.875

## MOTORIZED ELECTRIC STRIKE – MUNL

### Features

- Fits standard ANSI 4-78" strike cutout
- Lifetime replacement warranty
- Power consumption @ 12VDC 40mA continuous, minimum 700mA when motor is operating
- Power consumption @ 24VDC 40mA continuous, minimum 500mA when motor is operating
- No cutting on the jamb required
- Voltage 12 & 24 VDC or +29% - 10% full wave rectified DC acceptable
- Motorized, no solenoids
- Fully concealed installation
- Maintains dead-latch function at all times
- Releases under pre-load
- Latch status sensor is standard
- One model works with all North American Moritse Locks\*
- UL Listed

\*Sargent 7800 and 8200 require tab kit model #STK-1 for retrofit installations

### Options

- 12 VDC or 24 VDC



## MOTORIZED ELECTRIC STRIKE – MUNL (cont'd)

**Operating Temperature**  
-20 to 125F

### How to Order

<u>Part Number</u>	<u>Product Description</u>
MUNL-12	Mortise Unlatch, 12 VDC
MUNL-24	Mortise Unlatch, 24 VDC
STK-1	Tab Kit

Add -US3 for Polished Brass Finish and -10B for Oiled Bronze Finish

## ARCHITECTURAL SPECIFICATION – Motorized Electric Strike Model MUNL

### 2.x ELECTROMECHANICAL LOCK

- A. The electromechanical lock shall be manufactured by Securitron Magnalock Corp., Sparks, NV, an ISO 9001 certified manufacturer.
- B. The lock shall be available in a 12VDC and a 24VDC model.
- C. The lock shall have a lifetime replacement warranty.
- D. The lock shall fit into a standard ANSI cutout with little or no modification to the door frame.
- E. The lock shall be fail secure and shall maintain a higher security standard than a standard electric strike.
- F. The lock shall work with any mortise lock set manufactured for the U.S. market.
- G. The lock shall be rated at 250,000 or greater cycles of operation.
- H. The lock shall manipulate the latch and dead latch out of the strike without the use of solenoids or drop away paddles.
- I. The lock shall have an integrated lock status monitor with a form C output.